

# WorkForce AL-C300TN

DATASHEET



For small and medium workgroups wanting to lower their printing costs, this printer delivers fast and high-quality results. With gigabit Ethernet connectivity and both PCL6 and PostScript 3 emulations, it offers easy business integration. High-yield toner packs also help to keep the cost of printing low, and double-packs of black toner are available for even better cost savings.

### Fast, high-quality and low-cost printing

The AL-C300TN delivers ISO print speeds of up to 31ppm, in both mono and colour<sup>1</sup>. Prints are delivered at 1200 x 1200 dpi for high-quality results, and 1GB of RAM as standard saves time on repeated print jobs.

### Easy to use and energy efficient

Its LCD screen makes it easy to control advanced functions. A high toner yield of up to 7,300 pages in black and 8,800 pages in colour<sup>2</sup> not only makes your supplies go further, but it also means less time is wasted changing supplies. A double pack of black toner is also available. Not only is the AL-C300TN ENERGY STAR-qualified, it also has a very low power used of 1.3W when in deep sleep mode.

### High durability

It has a duty cycle of up to 120,000 pages<sup>3</sup>, so businesses can be confident that their investment in the Epson range is a sound one.

### Advanced connectivity, integration and security

PDL printer emulations including PCL6, PostScript 3 and PDF 1.7, along with the advanced IPv6 protocol and gigabit Ethernet support, make this printer ideal for business environments. Advanced IPsec and SSL support help improve security when printing sensitive materials, and print securely and confidentially with Email Print for Enterprise compatibility<sup>4</sup>.

## KEY FEATURES

- **Fast printing**  
ISO print speeds of up to 31ppm<sup>1</sup>
- **PDL printer emulations**  
Including PCL6, PostScript 3 and PDF 1.7
- **High toner yield**  
Print up to 7,300 pages in black and 8,800 pages in colour
- **High paper capacity**  
Holds up to 850 sheets
- **Reliable operation**  
120,000 page duty cycle

## PRODUCT SPECIFICATIONS

<b>TECHNOLOGY</b>	
Printing Resolution	1.200 x 1.200 dpi
Category	Department
<b>PRINT</b>	
Printing Speed	31 Pages/min Monochrome single-sided, 31 Pages/min Color single-sided
Max Duty cycle	120.000 Pages per month
First Page Out	Monochrome 12 Seconds
Warm Up time	38 s
<b>CONNECTIVITY</b>	
Interfaces	USB 2.0 Type B, USB host, Ethernet Interface (1000 Base-T/ 100-Base TX/ 10-Base-T)
Network Printing Protocols	LPR, FTP, IPP, Port 9100, WSD, Net BIOS over TCP/IP, TCP/IPv4, TCP/IPv6, IPsec
Network Management Protocols	SNMP, HTTP, DHCP, BOOTP, APIPA, DDNS, mDNS, SNTP, SSDP, Ping, SLP, WSD, LLTD, TCP/IPv4, TCP/IPv6, IPsec, IEEE 802.1X
<b>PAPER / MEDIA HANDLING</b>	
Paper Formats	A4, A5, A6, B5, C6 (Envelope), DL (Envelope), LT, HLT, LGL, GLG, GLT, EXE, F4, User defined, Com-10
Duplex	No
Compatible Paper Weight	60 g/m <sup>2</sup> - 210 g/m <sup>2</sup>
Standard Paper input	850 Sheets Standard, 100 Sheets MP tray, 750 Sheets paper tray
Output Tray Capacity	200 Sheets
Paper Tray Capacity	850 Sheets Standard, 850 Sheets maximum
Number of Paper Trays	3 Trays
Maximum paper input	850
<b>GENERAL</b>	
Product dimensions	444 x 544 x 350 mm (Width x Depth x Height)
Product weight	34,5 kg
Power consumption	910 W (Max.), 475 W (Printing), 69 W (Ready), 2,8 W (sleep), 1,34 W spectextmanualdeepsleep
Temperature	Operation 10° C - 30° C
Humidity	Operation 15% - 85%, Storage 35% - 70%
Compatible Operating Systems	Linux, Mac OS X 10.6.8 or later, Windows 7, Windows 8, Windows 8.1, Windows Server 2003 (32/64bit), Windows Server 2008 (32/64bit), Windows Server 2008 R2, Windows Server 2012 (64bit), Windows Server 2012 R2, Windows Vista, Windows XP
Drivers	Printer driver (PCL6, PS3)
Safety Standards	IEC60950-1, EN60950-1, IEC60825-1, EN60825-1
EMC Standard	IEC61000-4-3, IEC61000-4-4, IEC61000-4-5, IEC61000-4-6, IEC61000-4-8, IEC61000-4-11
EMI Standard	EN55022, EN55024, EN61000-3-2, EN61000-3-3
Included Software	EpsonNet Config
Sound Power	Operation: 6,9 B (A) - standby: 5,2 B (A)
Sound Pressure	Operation: 54 dB (A)-standby: 39 dB (A)
<b>OTHER FEATURES</b>	
Processor Speed	750 MHz
Memory	1 GB included, 1 GB maximum
Emulations	PCL5c, PCL5e, PCL6, PostScript 3, PDF 1.7
<b>OTHER</b>	
LCD screen	Type: Monochrome, 22 characters x 5 Lines
Resident type interface	84 ESC/page, 136PS3

## LOGISTICS INFORMATION

SKU	C11CE09401BW
Barcode	8715946544342

Epson Deutschland GmbH  
Otto-Hahn-Str. 4  
D-40670 Meerbusch  
Info-Line: 02159 92 79 500  
Telefax: +49 (0) 2159/538-3000  
www.epson.de

Epson in Österreich  
Info-Line: 01 253 49 78 333  
www.epson.at  
Epson in der Schweiz  
Info-Line: 022 592 7923  
www.epson.ch

Alle Marken und eingetragenen Warenzeichen sind das Eigentum der Seiko Epson Corporation oder der jeweiligen Rechteinhaber.  
Diese Produktinformationen können ohne vorherige Ankündigung geändert werden.

## WorkForce AL-C300TN

### WHAT'S IN THE BOX

- Main unit
- User manual (CD)
- Driver and utilities (CD)
- Software (CD)
- Warranty document
- Power cable

### SUPPLIES

- Color Laser Paper A4 - 10 x 250Sh  
C13S041163
- Color Laser Coated Paper A4 - 4 x 250Sh  
C13S041373
- WorkForce AL-C300 Fuser Unit  
C13S053061 (100.000 ( ))
- WorkForce AL-C300 Yellow Toner Cartridge  
C13S050747 (8.800 ( ))
- WorkForce AL-C300 Magenta Toner Cartridge  
C13S050748 (8.800 ( ))
- WorkForce AL-C300 Black Toner Cartridge  
C13S050750 (7.300 ( ))
- WorkForce AL-C300 Cyan Toner Cartridge  
C13S050749 (8.800 ( ))
- WorkForce AL-C300 Black Double Toner Cartridge Pack  
C13S050751 (14.600 ( ))
- AL-C300/C3900N/CX37DN series Photoconductor Unit Yellow  
C13S051201 (30.000 ( ))
- AL-C300/C3900N/CX37DN series Photoconductor Unit Magenta  
C13S051202 (30.000 ( ))
- AL-C300/C3900N/CX37DN series Photoconductor Unit Cyan  
C13S051203 (30.000 ( ))
- AL-C300/C3900N/CX37DN series Photoconductor Unit Black  
C13S051204 (30.000 ( ))
- AL-C300/C3900N/CX37DN series Waste Toner Bottle 36k (Mono) / 9k (Colour)  
C13S050595

1. Determined in accordance with ISO/IEC 24734 showing the average of ESAT / FSOT from the Office Category Test for default simplex /duplex. For more information visit [www.epson.eu/testing](http://www.epson.eu/testing) 2. Approx. page yield based on ISO/IEC 19752/19798. For more information visit <http://www.epson.eu/pageyield> 3. The maximum number of printed pages per month based on the performance capabilities of the printer, including ISO rated print speeds and paper handling capabilities 4. Please visit [www.epson.eu/epe](http://www.epson.eu/epe) for more information.

**EPSON**<sup>®</sup>